



500 HIGH FLOW CUTTER HEAD

Skid Steer Cutter Head



LEAN GREEN MULCHING MACHINES

Gyro-Trac brings its patented fixed-tooth planar-head cutting technology to the high-flow skid steer market with the 500HF cutter head.

The 500HF, the standard cutter head shipped with our medium-duty GT-13 mulching machine is now available for High-Flow skid steers and compact track loaders with 132 litres of hydraulic flow per minute and up. The 500HF mounts quickly and easily on any high-flow skid steer without the need for special hoses or couplings and can eliminate 300mm diameter softwoods and hardwoods up to 250mm in diameter.

With the 500HF, you can...

- Cut a tree AND completely mulch it into fine chips — in just a few minutes
- Grind dozens of stumps to the ground — in less than half a day
- Perform rapid, high-quality, low-cost right-of-way maintenance
- Cut miles of survey lines or fence lines for less than any other method
- Clear acres of small trees and underbrush in a single day
- Outperform any high-flow skid steer cutter head attachment on the market — guaranteed

Gyro-Trac's 500HF high-flow mulching attachment will clear more small trees and heavy brush in less time, with far less weight and fuel than any other attachment in its class. The 500HF utilizes a standard "quick-attach" for fast and dependable connections to almost any skid steer on the market.

The 500HF cutter head uses the same revolutionary technology as our GT-25XP — a 260 HP, 10ton heavy duty mulching machine that outperforms ANY forty-thousand-pound and up, 500-600 H.P. mega-mulcher on the market today — by a margin of over 2 to 1! Just imagine what our low-cost, high-performance cutter head will do for you! You'll never want to use a conventional brush cutter or stump grinder again — ever!



STANDARD SPECIFICATIONS



DIMENSIONS*

Cutting Width	1630 mm
Overall Width	1960 mm
Overall Height	1730 mm
Overall Depth	1300 mm
Weight	1089 kg

PERFORMANCE*

No. of Teeth	23
Recommended RPM	2350
Hydraulic HP	80 - 140 HP variable
Maximum Flow	189 Lpm
Minimum Flow	113 Lpm

FOR USE ONLY WITH SKID STEERS EQUIPPED WITH ENCLOSED CABS.
Certain applications may require SAE-certified ROPS/FOPS skid steers.

* All specifications are preliminary and are subject to change without notice.

FEATURES AND BENEFITS

- Patented fixed-tooth planar cutting head outperforms the competition by as much as 2 to 1 "Quick-Attach" — mounts quickly on any skid steer
- Low-cost, high-performance and easily-replaceable teeth
- No need for hydraulic adjustments, works at almost any horsepower and flow — just "Attach & Go!"

hydromulch (PTY) LTD
Planting the Seed of Environmental Success

+27 11 964 2582
info@hydromulch.co.za
www.hydromulch.co.za